

# ADNOC ATF DEXRON III

## DESCRIPTION

ADNOC ATF Dexron III-H is a high performance, multifunctional, automatic transmission fluid formulated with full synthetic base oils and specially selected additives that provide optimal friction properties as well as protection against corrosion, wear, sludge, deposits and lubricant oxidation.

## APPLICATIONS

ADNOC ATF Dexron III-H is suitable for passenger car and commercial vehicle automatic transmission, hydraulic systems of mobile and off-high way equipment and industrial equipment applications that required the following specifications.

## BENEFITS

- › Optimal friction properties provide smooth shifting and trouble free operations
- › Excellent oxidation resistance resulting in cleaner transmissions
- › Compatible with all types of rubbers, elastomers and metals and providing protection against wear and leakage
- › Excellent low-temperature fluidity
- › Good shear stability

## PERFORMANCE

Allison C-4, TES 389  
 GM Dexron® III-H  
 Ford Mercon®

## TYPICAL PRODUCT CHARACTERISTICS

Property	Value (Typical)
Density @15°C	0.854
Kinematic Viscosity @40°C	34.30
Kinematic Viscosity @100°C	7.300
Viscosity Index	185
Pour Point	-42
Flash Point, COC	200
Color	Red

Data for reference only. Consult Lubesouq for current OEM specifications.