

ADNOC AUTOCOOL 50%

DESCRIPTION

ADNOC AUTOCOOL is recommended for use in liquid cooling systems of automotive and industrial gasoline and diesel engines. They are available in various concentrations ready for use. It is harmless to rubber and does not foam or clog radiators. Based on OAT (Organic Acid Technology) chemistry. Free from Nitrates and Amines.

APPLICATIONS

ADNOC AUTOCOOL protects cooling systems of gasoline and diesel engine against rust in all seasons. It provides ideal cooling, effective protection against corrosion and scale deposit formation in the cooling systems year-round, resulting in longer radiator life.

ADVANTAGES

- High boiling point gives better cooling performance in high temperature condition.
- Excellent anti-foam properties.
- Protects the radiator against rust & corrosion.
- Compatible with ordinary summer coolant.
- Protection against excessive evaporation.
- Provides year round cooling properties

PERFORMANCE

BS 6580
ASTM D3306

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (50%)
AUTOCOOL LL	50%
Specific Gravity @ 20 Deg Celcius	1.072
Reserve Alkalinity, ASTM D1121	1.3
Density at 20 Deg Celcius ASTM D 4052	1.070
pH value (33%) ASTM D1287	8.22
Freezing Protection (50%), oC ASTM D1177	-42
Foam, break time (ASTM D1881)	<2
Amine	<0.1
Borate	<1
Silicate	3
Nitrate	<2
Flash point, COC oC	112
Colour	Blue

Data for reference only. Consult Lubesouq for current OEM specifications.