

ADNOC GEAR OIL GP 85W/90 GL-4 (56290)

SAE 85W-90

DESCRIPTION

ADNOC Gear Oil GP is a series of automotive gear lubricants formulated from highly refined base oils and carefully selected additives based on extreme pressure sulfur-phosphorous chemistry that provide protection against rust, corrosion and wear over a wide range of temperature and service conditions.

APPLICATIONS

ADNOC Gear Oil GP is recommended for manual transmissions fitted in passenger cars and on/off-road vehicles, operating under high speed, low torque and low-speed/high torque conditions. It can be used in as a rear axle lubricant under low/medium severity like passenger cars and light duty vehicles that require API GL-4 specification. It is not recommended for conventional heavy duty hypoid axles operating under high loads/high severity, except when specified by the manufacturer a product with such characteristics.

BENEFITS

- › Formulated for automotive high speed gears
- › Excellent lubrication even at low temperatures
- › Provides good protection against corrosion and wear
- › Good thermal stability and resistance to high temperature oxidation

PERFORMANCE

API GL-4

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (SAE 85W-90)
Density @15°C	0.901
Kinematic Viscosity @40°C	200.0
Kinematic Viscosity @100°C	17.50
Viscosity Index	96
Pour Point	-15
Flash Point, COC	220

Data for reference only. Consult Lubesouq for current OEM specifications.