

ADNOC GREASE LX EP 2

2

DESCRIPTION

ADNOC Grease LX EP is an extreme pressure Lithium Complex soap grease which contains oxidation, rust and corrosion inhibitors and provides excellent EP properties. The use of a lithium complex soap base ensures effective resistance to softening under severe working conditions, efficient water resistance and a consistency which remains relatively constant over the recommended range of operating temperatures. It is non-corrosive to both steel and copper and exhibits effective resistance to bleeding and superior resistance to water washout.

APPLICATIONS

ADNOC Grease LX EP is recommended for lubrication of plain and rolling element bearings in normal through heavy-duty industrial applications. It is suitable where loads are high or shock loads are present. It resists water washing and provides rust protection for bearings if water is present. It is suitable for use in a number of industrial and automotive applications including,

BENEFITS

- › Superior lubrication under heavy and shock loading conditions
- › Longer life at higher temperatures
- › Resists softening at elevated temperatures
- › Excellent load carrying ability
- › Excellent resistance to water washing
- › Effective rust protection and corrosion resistance

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (2)
Texture	Smooth
Thickener Type	Lithium Complex Soap
Base Oil Type	Mineral
Base Oil Viscosity @40°C	190.0
Base Oil Viscosity @100°C	17.00
Dropping Point, Min.	265
Worked Penetration @25°C	280
Oil Separation	2
Water Washout	5
Four-Ball Welding Load	>270
Operating Temp, Min.	-20
Operating Temp, Max.	+160

Data for reference only. Consult Lubesouq for current OEM specifications.