

ADNOC GX 85W/140 GL5

SAE 85W-140

DESCRIPTION

ADNOC Gear Oil GX is a series of automotive gear lubricants formulated from highly refined base oils and carefully selected additives based on extreme pressure sulfur-phosphorous chemistry that provide protection against rust, corrosion and wear over a wide range of temperature and service conditions.

APPLICATIONS

ADNOC Gear Oil GX is recommended for manual transmissions, differentials, hypoid gear axles and final drives fitted in passenger cars, on/off-road and commercial vehicles, operating under high speed/ shock loads, high speed/low torque and low-speed/ high torque conditions, where API GL-5 specification is required. It is not recommended for manual transmissions that use synchronizers made of yellow metals that require API GL-4 specification.

BENEFITS

- › Excellent protection against wearing and scoring produced by high speed and heavy loads
- › Multi-viscosity grades provide good lubrication even at low temperatures
- › Provides good protection against corrosion and wear
- › Good thermal stability and resistance to high temperature oxidation
- › Excellent load carrying capacity and good antifoam properties
- › Maximizes equipment service life
- › Suitable for a wide variety of applications and service conditions
- › Compatible with seals and gaskets

PERFORMANCE

API GL-5

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (SAE 85W-140)
Density @15°C	0.909
Kinematic Viscosity @40°C	405.0
Kinematic Viscosity @100°C	28.25
Viscosity Index	96
Pour Point	-12
Flash Point, COC	220

Data for reference only. Consult Lubesouq for current OEM specifications.