

ADNOC VOYAGER GOLD 5W/40 SN

SAE 5W-40

DESCRIPTION

ADNOC Voyager Gold is a top of the range, multigrade, shear-stable, formulated with high quality full synthetic base oils and latest generation additives designed to provide maximum engine protection against wear, deposits build up, sludge and varnish formation. It provides long service intervals and trouble free operation and keeps engine's performance at its maximum throughout the full oil service life even operating under severe conditions.

APPLICATIONS

ADNOC Voyager Gold is recommended for petrol and diesel engines of passenger cars, vans, light duty trucks and 4WD recreational vehicles. It is suitable for high performance engines with high power density, especially those fitted with turbochargers and superchargers. It can be used in modern and old models of American, European, Japanese, Korean and other automobile makers that require the following specifications. It is not recommend for light duty diesel engines equipped with DPF (Diesel Particulate Filter).

BENEFITS

- › Exceptional thermal stability and oxidation resistance
- › Low oil consumption and long drain intervals with outstanding protection against wear, rust, corrosion and exceptional engine cleanliness
- › Multi-viscosity characteristic ensure rapid oil circulation on start-up the engine
- › Outstanding low temperature fluidity, excellent shear stability and stable viscosity during operation
- › Strong oil film minimizes metal to metal contact
- › Superior protection of exhaust emission control system, that maximizes three-way catalyst lifespan.

PERFORMANCE

SAE 5W-30; 0W-40; 5W-40

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (SAE 5W-40)
Density @15°C	0.856
Kinematic Viscosity @40°C	83.00
Kinematic Viscosity @100°C	14.00
Viscosity Index	174
CCS Viscosity	5000
- CCS Temperature	-30
Pour Point	-39
Flash Point, COC	235

Data for reference only. Consult Lubesouq for current OEM specifications.