

VOYAGER HPSD PLUS 15W40 CH-4

SAE 15W-40

DESCRIPTION

ADNOC Voyager HPSD Plus CH-4 is a series of heavy duty diesel engine oils, developed primarily for high output naturally aspirated or supercharged diesel engines, operating under severe conditions. It is formulated from high quality base oils and chemical additives to provide protection against wear and lubricant thermal breakdown.

APPLICATIONS

ADNOC Voyager HPSD Plus CH-4 is recommended for use in high-output diesel engines fitted in automotive, agricultural, mining and construction equipment, operating in fleet and construction business where relatively high sulfur fuel is used and other severe service factors are considered. It is suitable for old diesel engines operating in both cold and hot climates and is also recommended for land based water pump diesel engines operating under severe service conditions. Its high Base Number is well suited for high sulfur diesel fuels considering the appropriate oil drain intervals.

BENEFITS

- › Excellent protection against the effects of high- sulfur fuels
- › Good control on high temperature deposits
- › Improved resistance to ring sticking, ring and cylinder wear, valve and combustion deposits
- › Low oil consumption
- › Minimizes bore polishing effect

PERFORMANCE

API CH-4/SJ

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (SAE 15W-40)
Density @15°C	0.881
Viscosity Index	140
CCS Viscosity	6500
- CCS Temperature	-20
Pour Point	-27
Flash Point, COC	230
Base Number	10

Data for reference only. Consult Lubesouq for current OEM specifications.