

ADNOC VOYAGER SILVER 10W/40 SL

SAE 10W-40

DESCRIPTION

ADNOC Voyager Silver is a high quality, multigrade, shear-stable, semi-synthetic engine oil designed to provide maximum engine protection against wear, deposits build up, sludge and varnish formation. It provides long service intervals and trouble free operation and keeps engine's performance at its maximum throughout the full oil service life even operating under severe conditions.

APPLICATIONS

ADNOC Voyager Silver is recommended for petrol and diesel engines of passenger cars, vans, light duty trucks and 4WD recreational vehicles. It is suitable for high performance engines with high power density, especially those fitted with turbochargers and superchargers. It is suitable and exceeds the performance requirements of most European, Japanese and American car manufacturers that require the following specifications. It is not recommended for light duty diesel engines equipped with DPF (Diesel Particulate Filter).

BENEFITS

- › Exceptional thermal stability and oxidation resistance
- › Low oil consumption and long drain intervals with outstanding protection against wear, rust, corrosion and exceptional engine cleanliness
- › Multi-viscosity characteristic ensure rapid oil circulation on start-up the engine
- › Easy cold start and ideal. Lubrication at elevated temperatures ensures low oil consumption and cold start protection against wear.
- › High Viscosity Index and excellent shear stability results in stable viscosity during operation.

PERFORMANCE

ACEA A3/B4
 API SN
 MB 229.1/229.3
 Renault RN0700/0710
 VW 501 01 / VW 505 00

TYPICAL PRODUCT CHARACTERISTICS

Property	Value (SAE 10W-40)
Density @15°C	0.860
Kinematic Viscosity @40°C	95.85
Kinematic Viscosity @100°C	14.54
Viscosity Index	157
CCS Viscosity	6000
- CCS Temperature	-25
Pour Point	-33
Flash Point, COC	230

Data for reference only. Consult Lubesouq for current OEM specifications.